

Hand Dryer unit	Specifications	
Finishes	White & UV coating	
	Silver & UV coating	
	Black & UV coating (Limited Edition)	
Construction	Materials	Fireproof 94VO, ABS
	Anti microbial agent	IONPURE antimicrobial metal ions
	Net Weight	2.6kg
	Packed Weight	3.2kg
Dimensions	Product Height	323mm
	Product Width	271mm
	Product Depth	145mm
	Packaging Height	395mm
	Packaging Width	320mm
	Packaging Depth	200mm
Energy Consumption	Electrical Supply Voltage	220-240 volts / 110-120 volts
	Electrical Supply Frequency	50/60Hz
	Standby Power Consumption	<0.5 Watts (Blue angel regulation)
Performance	Minimum motor life span	5000 hours
	Dry time	12 Seconds (max settings)
	Motor	Digital Brushless DC Motor (BLDC)
	Motor Speed	30,000 RPM
	Air Speed	96 m/s (345km/h)
	Air Volume	84 m³/h
	Operating Temperature Range	Thermal protection auto resetting : 120°C
	Heater element Power	0- / 400 Watts
	Motor Cut-off Time	50 Seconds
	Motor Class	Class 1
	Operating Sound Level	72 dB at 1 meter
Rated Power	Rated Power (min setting)	300 Watts
	Rated Power with heater on	720 Watts
Certification	CE,ETL,RoHS (TUV certified) marked in accordance with EEC documents, Q mark	
LED Light Scheme	White & Silver	
	Standby mode	Working mode
	1 white LED on	6 white LED moving
	Black edition	
	Standby mode	Working mode
	1 red LED on	6 red LED moving
Clean Air Filter	Material : HEPA (H13) filter media + Antimicrobial filter	
	Filter replacement alert system and indication lights	
Pointing Light	Blue LED when working mode, blinking after 75,000 uses for Filter replacement alert	
Heater Switch	Included on the main control board	
Waterproof level	IPX3	
Sensing distance	10~25cm	
Timing Protection	50 sec. auto shut off	
Manuals	User manual, installation manual, installation templet, filter installation manual	
	Languages available : EN,DE,FR,ES,TR,KO,JP	
Packaging	Paced Weight	3.2 kg
	Package cushioning	Moulded paper cushioning