

GWHD22AS (DIAMOND+)



Hand Dryer unit	Specifications	
Finishes	Silver & Anodizing	
	Black & Anodizing	
	Rose Gold & Anodizing	
	White & Coating (Limited Edition)	
Construction	Materials	Aviation Aluminum (Anodizing)
	Net Weight	2.6kg
	Packed Weight	14kg (4units per Carton)
Dimensions	Product Height	272mm
	Product Width	136mm
	Product Depth	123mm
	Packaging Height	410mm
	Packaging Width	405mm
	Packaging Depth	340mm
Energy Consumption	Electrical Supply Voltage	220-240 volts / 110-120 volts
	Electrical Supply Frequency	50/60Hz
	Standby Power Consumption	<0.5 Watts (Blue angel regulation)
Performance	Minimum motor life span	5000 hours
	Dry time	12 Seconds (max settings)
	Motor	Digital Brushless DC Motor (BLDC)
	Motor Speed	30,000 RPM
	Air Speed	98 m/s
	Air Volume	85 m³/h
	Operating Temperature Range	Auto reset safety overload against 115 °C
	Heater element Power	400 Watts @230V, 500 Watts @120V
	Motor Cut-off Time	50 Seconds
	Operating Sound Level	≤75dB(A) at 1 meter
Rated Power	Rated Power (min setting)	320W
	Rated Power with heater on	720Watts @AC230V, 820W @AC120V
Pointing Light	Blue LED for pointing air blow range, White LED for stand by, Blue LED for operating	
Clean Air Filter	Material : HEPA (H13) filter media + Antimicrobial filter	
	Filter replacement alert system and indication lights	
Heater Switch	Yes, switch on main board	
Speed control switch	Yes	
Power switch	Yes	
UV lamp (option)	254nm UV lamp	
Plasma Generator(option)	≥200,000 PCS/cm³@ 1m, DC12V	
Waterproof level	IPX3	
Electrical isolation	Class I	
Sensing distance	45° 10~20cm	
Certification	CE EMC,CE LVD,CB,ROSH	

